

Grease List - Lubrication Recommendation

The SIMPLEX seal is fitted with sealing rings of NBR, HNBR or FKM depending on the operating conditions.

The suitable sealing materials for the greases are marked with "X".

Product Name	For Use With			Type	Remarks
	NBR (Perbunan)	FKM (Viton)	HNBR		
BP					
Energrease MP-MG 2	X	X	-	S	
Castrol					
BioTac MP	-	X**	-	B	
Spheerol SX 2	X	X	-	S	
Klüber					
Altemp Q NB 50	-	-	-	S	Approved for use as mounting grease
Klüber Isoflex Topas NB 152	X	X	X	S	
Klüberbio M72-501	-	X**	-	B	
Klüberbio M72-82	-	X**	-	B	
Microlube GL 261	X	X*	-	S	
Microlube GL 262	-	X*	-	S	
Petamo GHY 133 N	-	X	-	S	
Staburags NBU 12K	X	-	-	S	
Staburags NBU 30K	X	X**	-	S	
Stabutherm GH 461	X**	X*	-	S	
ExxonMobile					
Mobilgrease EAL 102	-	X**	-	B	
Mobilgrease XHP 222	X	X	-	S	
Mobilux EP 2	X	-	-	S	
Panolin					
Margrease EPO	-	X**	X**	B	
Shell					
Alvania EP (LF) 2	-	-	-	S	Approved for use as mounting grease
Aseol Aquares EP 2	X	X*	-	S	
Retinax LX2	X	X	-	S	
SRS 4000	X	X*	-	S	
Trustlube					
Xtreme Offshore Grease	X	X	X	S	
Vickers					
Biogrease EP2	-	-	-	B	Test running

* At continuous use with T > 100°C please consult SKF Marine GmbH.

** Application in consultation with SKF Marine GmbH only.

B Biodegradable grease/ Seal lubricant

S Standard grease/ Seal lubricant

X Approved

For further information please get in contact with your local sales agent. Please ask SKF Marine GmbH for approval before use of another grease to achieve reliable operation with your individual sealing system.

SKF Marine GmbH

Hermann-Blohm-Straße 5, D-20457 Hamburg